






































Crest Industries, Inc. Saint Louis, Missouri

To Re-Order Call:
800-733-2737 636-349-4800
www.crestmidwest.com



Grease Fittings and Fender Washers

CRA 634

<p>CRX9404 1/4-28 SAE STRT GREASE FIT 9/16 OAL</p> <p>1/4"-28 Straight Grease Fitting Thread Length: 7/32" Overall Length: 9/16" Ball Check, Plated Qty/50</p>  <p>50 PKG</p> 	<p>CRX9388 1/8-27 NPT STRT GREASE FIT 1-1/4 OAL 1/8 Pipe St. Ind. Ref. # 1607 Overall Length: 1 - 1/4 Grease Fittings</p>  <p>25 PKG</p> 	<p>CRX9398 1/4-28 SAE 90 DEG GREASE FIT 45/64 OAL 1/4 - 28, 90 Degree Ind. Ref #1911 Overall Length: 45/64 Grease Fittings Plated</p>  <p>25 PKG</p> 	<p>CRX13654 M8-1.25 Straight Grease Fitting 15mm OAL M8-1.25 Straight Ind. Ref. #9201 Grease Fittings Plated</p>  <p>10 PKG</p> 	<p>CRX6755-TKX 3/16X1 X-THICK FENDER WASHER ZC 3/16" X 1" Extra Thick Fender Washer Bolt Size: 1/4" Inside Diameter: 7/32" Outside Diameter: 1" Thickness: .108/.132" Zinc Clear</p>  <p>50 PKG</p> 	<p>CRX6758-TK 1/4X1 THICK FENDER WASHER ZC 1/4" X 1" Thick Fender Washer Bolt Size: 1/4" Inside Diameter: 9/32" Outside Diameter: 1" Thickness: .051/.084" Zinc Clear</p>  <p>50 PKG</p> 
<p>CRX9408 1/4-28 SAE STRT GREASE FIT 15/16 OAL 1/4 - 28, Straight Ind. Ref. #1680 Overall Lgth 15/16 Grease Fittings</p>  <p>25 PKG</p> 		<p>CRX10454 1/8-27 NPT STRAIGHT GREASE FITTING XS Zerk, Straight, 1/8-27 PTF Special Extra Short, Steel, Zinc Yellow, SAE J534, Check: Surface Ball, OAL: 0.66, Shank: 0.28 Standard, Drive: 7/16 Hex</p>  <p>25 PKG</p> 	<p>CRX9402 1/8-27 NPT 65 DEG GREASE FIT 7/8 OAL 1/8 Pipe; 65 Degrees Ind. Ref. #1612 Overall Lgth: 7/8 Grease Fittings</p>  <p>25 PKG</p> 	<p>CRX6760-TK 1/4X1-1/4 THICK FENDER WASHER ZC 1/4" X 1-1/4" Thick Fender Washer Bolt Size: 1/4" Inside Diameter: 9/32" Outside Diameter: 1-1/4" Thickness: .051/.084" Zinc Clear</p>  <p>50 PKG</p> 	<p>CRX6762 1/4X1-1/2 FENDER WASHER ZC 1/4" X 1-1/2" Fender Washer Bolt Size: 1/4" Inside Diameter: 9/32" Outside Diameter: 1-1/2" Thickness: .036/.056" Zinc Clear</p>  <p>50 PKG</p> 
<p>CRX9396 1/4-28 SAE 45 DEG GREASE FIT 29/32 OAL</p> <p>1/4-25, 45 Degree Overall Length: 29/32" Ball Check, Plated Qty/25</p>  <p>25 PKG</p> 	<p>CRX10450 1/8-27 NPT 30 DEGREE GREASE FITTING 1/8" 30 Degree Grease Fitting Qty/50</p>  <p>50 PKG</p> 	<p>CRX9392 1/8-27 NPT 45 DEG GREASE FIT 1.0 OAL 1/8 Pipe, 45 Degrees Ind Ref. #1688 Overall Length: 1 Grease Fittings</p>  <p>25 PKG</p> 	<p>CRX9386 1/8-27 NPT 90 DEG GREASE FIT 53/64 OAL 1/8 Pipe, 90 Degrees Ind Ref. #1613 Overall Length: 53/64 Grease Fittings</p>  <p>25 PKG</p> 	<p>CRX6770-TK 5/16X1-1/4 THICK FENDER WASHER ZC 5/16" X 1-1/4" Thick Fender Washer Bolt Size: 5/16" Inside Diameter: 11/32" Outside Diameter: 1-1/4" Thickness: .051/.084" Zinc Clear</p>  <p>50 PKG</p> 	<p>CRX6772 5/16X1-1/2 FENDER WASHER ZC 5/16" X 1-1/2" Fender Washer Bolt Size: 5/16" Inside Diameter: 11/32" Outside Diameter: 1-1/2" Thickness: .036/.056" Zinc Clear</p>  <p>50 PKG</p> 
				<p>CRX6790 3/8X1-1/2 FENDER WASHER ZC 3/8" X 1-1/2" Fender Washer Bolt Size: 3/8" Inside Diameter: 13/32" Outside Diameter: 1-1/2" Thickness: .036/.056" Zinc Clear</p>  <p>100 PKG</p> 	<p>CRX6801 1/2X1-1/2 FENDER WASHER ZC 1/2" X 1-1/2" Fender Washer Bolt Size: 1/2" Inside Diameter: 17/32" Outside Diameter: 1-1/2" Thickness: .036/.056" Zinc Clear</p>  <p>100 PKG</p> 