

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23
Version: 4.0

Page: 1/13
(30277416/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

93430 1K Clr Plastic AdPro

Recommended use of the chemical and restriction on use

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Flam. Liq.	3	Flammable liquids
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
STOT RE	2	Specific target organ toxicity — repeated

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 2/13

(30277416/SDS_GEN_US/EN)

exposure

Label elements

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs (Auditory organ, Central nervous system, Kidney, Liver) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 3/13

(30277416/SDS_GEN_US/EN)

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

1,2,4-trimethylbenzene

CAS Number: 95-63-6

Content (W/W): ≥ 3.0 - $< 5.0\%$

Synonym: 1,2,4-Trimethylbenzene

cumene

CAS Number: 98-82-8

Content (W/W): ≥ 0.3 - $< 1.0\%$

Synonym: (1-Methylethyl)benzene; Isopropylbenzene, Cumene

ethylbenzene

CAS Number: 100-41-4

Content (W/W): ≥ 10.0 - $< 15.0\%$

Synonym: Ethylbenzene

Xylene

CAS Number: 1330-20-7

Content (W/W): ≥ 50.0 - $< 75.0\%$

Synonym: Xylene; Dimethylbenzene

Benzene, trimethyl-

CAS Number: 25551-13-7

Content (W/W): ≥ 7.0 - $< 10.0\%$

Synonym: Trimethylbenzene

Solvent naphtha (petroleum), light arom.

CAS Number: 64742-95-6

Content (W/W): ≥ 10.0 - $< 15.0\%$

Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23
Version: 4.0

Page: 4/13
(30277416/SDS_GEN_US/EN)

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: 1,2,4-trimethylbenzene

Symptoms: Overexposure may cause:, headache, tiredness, nausea, anxiety, asthma, bronchitis, noncardiogenic pulmonary edema

Information on: cumene

Symptoms: Overexposure may cause:, unconsciousness, coordination disorder, headache, dizziness

Information on: Xylene

Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Information on: Benzene, trimethyl-

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:, irritation of respiratory tract, coughing

Information on: Solvent naphtha (petroleum), light arom.

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 5/13

(30277416/SDS_GEN_US/EN)

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Page: 6/13

Version: 4.0

(30277416/SDS_GEN_US/EN)

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Benzene	ACGIH, US:	STEL value 2.5 ppm ;
	ACGIH, US:	TWA value 0.5 ppm ;
	OSHA Z2:	max. conc. 50 ppm ;
	OSHA Z2:	CLV 25 ppm ;
	OSHA Z2:	TWA value 10 ppm ;
	OSHA, US:	TWA value 1 ppm ;
	OSHA, US:	OSHA Action level 0.5 ppm ;
	OSHA, US:	STEL value 5 ppm ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
1,2,4-trimethylbenzene	ACGIH, US:	TWA value 25 ppm ;
cumene	OSHA Z1:	Skin Designation ; The substance can be absorbed through the skin.
	OSHA Z1:	PEL 50 ppm 245 mg/m3 ;
	ACGIH, US:	TWA value 5 ppm ;
ethylbenzene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
Xylene	ACGIH, US:	TWA value 100 ppm ;
	ACGIH, US:	STEL value 150 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
Benzene, trimethyl-	ACGIH, US:	TWA value 25 ppm ;

Advice on system design:

General mechanical ventilation should comply with OSHA 1910.94.

Provide local exhaust ventilation to maintain recommended P.E.L.

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 7/13

(30277416/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	aromatic	
Odour threshold:	No applicable information available.	
Colour:	clear	
	clear	
pH value:	Unspecified	
	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	136.67 - 171.00 °C	
	278.00 - 339.80 °F	
Sublimation point:	No applicable information available.	
Flash point:	27.78 °C	
	82.00 °F	
Flammability:	No applicable information available.	
Lower explosion limit:	1.10 %(V)	
Upper explosion limit:	6.60 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	7.2851 lb/USg	(calculated)
	(20 °C)	
	0.8742 g/cm3	(calculated)
	(20 °C)	
	7.2955 lb/USg	(calculated)
Relative density:	0.8742	
	(20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 8/13

(30277416/SDS_GEN_US/EN)

Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	> 20.500 mm ² /s
Solubility in water:	No applicable information available.
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1,2,4-trimethylbenzene

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 9/13

(30277416/SDS_GEN_US/EN)

Information on: cumene

Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Information on: ethylbenzene

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.

Information on: Xylene

Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.

Information on: Solvent naphtha (petroleum), light arom.

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. No deaths at the highest dose tested after short-term inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Of low toxicity after short-term skin contact.

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Information on: 1,2,4-trimethylbenzene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: cumene

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes. Causes temporary irritation of the respiratory tract.

Information on: ethylbenzene

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Information on: Solvent naphtha (petroleum), light arom.

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization

Assessment of sensitization: No applicable information available.

Aspiration Hazard

No applicable information available.

Chronic Toxicity/Effects

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23
Version: 4.0

Page: 10/13
(30277416/SDS_GEN_US/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Information on: Solvent naphtha (petroleum), light arom.

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion.

Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested.

The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: cumene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity: No applicable information available.

Teratogenicity

Assessment of teratogenicity: No applicable information available.

12. Ecological Information

Additional information

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Version: 4.0

Page: 11/13

(30277416/SDS_GEN_US/EN)

Other ecotoxicological advice:
Acutely toxic for aquatic organisms.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

Air transport

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23

Page: 12/13

Version: 4.0

(30277416/SDS_GEN_US/EN)

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
98-82-8	cumene
100-41-4	ethylbenzene
95-63-6	1,2,4-trimethylbenzene
1330-20-7	Xylene

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	95-63-6	1,2,4-trimethylbenzene
	100-41-4	ethylbenzene
	1330-20-7	Xylene
PA	71-43-2	Benzene
	95-63-6	1,2,4-trimethylbenzene
	100-41-4	ethylbenzene
	1330-20-7	Xylene
	25551-13-7	Benzene, trimethyl-

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including BENZENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

HMIS III rating

Health: 2^a Flammability: 3 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2021/08/23

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE

Safety Data Sheet

93430 1K Clr Plastic AdPro

Revision date : 2021/08/23
Version: 4.0

Page: 13/13
(30277416/SDS_GEN_US/EN)

MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET