

Revision date : 2019/08/28 Version: 4.0

Page: 1/12 (30660045/SDS\_GEN\_US/EN)

# 1. Identification

Product identifier used on the label

# 11-LE385 Magenta Shimmer

Recommended use of the chemical and restriction on use

Recommended use\*: for industrial use only

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

# Details of the supplier of the safety data sheet

<u>Company:</u> BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

# **Emergency telephone number**

CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP (4357)

### Other means of identification

# 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

# **Classification of the product**

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

# Label elements

Revision date : 2019/08/28 Version: 4.0 Page: 2/12 (30660045/SDS GEN US/EN)



Signal Word: Danger Hazard Statement: H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. Precautionary Statements (Prevention): P280 Wear protective gloves/protective clothing/eye protection/face protection. P271 Use only outdoors or in a well-ventilated area. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash with plenty of water and soap thoroughly after handling. P242 Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting/equipment. P241 P243 Take action to prevent static discharges. Keep container tightly closed. P233 Keep away from heat, hot surfaces, sparks, open flames and other P210 ignition sources. No smoking. P240 Ground and bond container and receiving equipment. P272 Contaminated work clothing should not be allowed out of the workplace. Precautionary Statements (Response): P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P370 + P378 In case of fire: Use water spray for extinction. P362 + P364 Take off contaminated clothing and wash it before reuse. P310 Immediately call a POISON CENTER or doctor/physician. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Precautionary Statements (Storage): P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Precautionary Statements (Disposal): P501 Dispose of contents/container to hazardous or special waste collection point.

# Hazards not otherwise classified

No applicable information available.

# 3. Composition / Information on Ingredients

# According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Weight %	<u>Chemical name</u>
107-98-2	>= 20.0 - < 25.0%	1-methoxypropan-2-ol
108-01-0	>= 1.0 - < 3.0%	2-dimethylaminoethanol
111-76-2	>= 1.0 - < 3.0%	2-butoxyethanol
126-86-3	>= 1.0 - < 3.0%	2,4,7,9-Tetramethyldec-5-yne-4,7-diol
7783-40-6	>= 7.0 - < 10.0%	Magnesium fluoride (MgF2)
108-65-6	>= 15.0 - < 20.0%	1-methoxy-2-propylacetate

# 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

Seek medical attention. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

# Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Revision date : 2019/08/28 Version: 4.0

# 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media: carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting: Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

# Advice for fire-fighters

Protective equipment for fire-fighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

# 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

#### **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

#### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

# 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Revision date : 2019/08/28 Version: 4.0

	Page: 5/12	
(30660045/SDS	GEN US/EN)	

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

# Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability: Consult local fire marshal for storage requirements. Protect from temperatures above: 49 °C

# 8. Exposure Controls/Personal Protection

#### **Components with occupational exposure limits**

1-methoxypropan-2-ol	OSHA PEL	TWA value 100 ppm 360 mg/m3;STEL value 150 ppm 540 mg/m3;
	ACGIH TLV	TWA value 50 ppm ; STEL value 100 ppm ;
2-butoxyethanol	OSHA PEL	PEL 50 ppm 240 mg/m3 ; Skin Designation ; The substance can be absorbed through the skin. SKIN_FINAL ; The substance can be absorbed through the skin. TWA value 25 ppm 120 mg/m3 ;
	ACGIH TLV	TWA value 20 ppm ;
Magnesium fluoride (MgF2)	OSHA PEL	PEL 2.5 mg/m3 (fluorine (F)); TWA value 2.5 mg/m3 (fluorine (F)); TWA value 2.5 mg/m3 dust ;
	ACGIH TLV	TWA value 2.5 mg/m3 (fluorine (F));
chromium	OSHA PEL	PEL 1 mg/m3 (Chromium (Cr)); TWA value 1 mg/m3 ;
	ACGIH TLV	TWA value 0.5 mg/m3 Inhalable fraction (Cr (0));

#### Advice on system design:

General mechanical ventilation should comply with OSHA 1910.94. Provide local exhaust ventilation to maintain recommended P.E.L.

#### Personal protective equipment

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Revision date : 2019/08/28 Version: 4.0

### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

# 9. Physical and Chemical Properties

Form:	liquid	
Odour:	amine-like	
Odour threshold:	No applicable information available.	
Colour:	various	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Boiling range:	118.89 - 171.11 °C	
	246.00 - 340.00 °F	
Sublimation point:	No applicable information available.	
Flash point:	32.22 °C	
-	90.00 °F	
Flammability:	No applicable information available.	
Lower explosion limit:	1.50 %(V)	
Upper explosion limit:	13.74 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.0793 g/cm3	(calculated)
	( 20 °C)	х ,
	9.0071 lb/USg	(calculated)
Relative density:	1.0793	. ,
-	( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-	No applicable information available.	
octanol/water (log Pow):		
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.600 mm2/s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	
- T	TT STOLE STOLENESS STOLENESS	

# **10. Stability and Reactivity**

#### Reactivity

No applicable information available.

#### Chemical stability

The product is chemically stable.

#### Revision date : 2019/08/28 Version: 4.0

# Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

#### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products: carbon dioxide, carbon monoxide

Thermal decomposition: No applicable information available.

# **11. Toxicological information**

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

<u>Primary routes of entry</u> Solvents are absorbed through the skin.

# **Acute Toxicity/Effects**

Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1-methoxypropan-2-ol

Assessment of acute toxicity:Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

#### Information on: 2-dimethylaminoethanol

Assessment of acute toxicity:Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation.

#### Information on: 2-butoxyethanol

Assessment of acute toxicity:Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified this substance as 'harmful' after inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after dermal exposure.

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Revision date : 2019/08/28 Version: 4.0

Information on: 1-methoxypropan-2-ol Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Information on: 2-dimethylaminoethanol Assessment of irritating effects: Corrosive! Damages skin and eyes.

Information on: 2-butoxyethanol Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol Assessment of irritating effects: Not irritating to the skin. May cause severe damage to the eyes.

Information on: Magnesium fluoride (MgF2) Assessment of irritating effects: Not irritating to eyes and skin.

Information on: 1-methoxy-2-propylacetate Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

<u>Sensitization</u> Assessment of sensitization: Sensitization after skin contact possible.

Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol Assessment of sensitization: Caused skin sensitization in animal studies.

-----

<u>Aspiration Hazard</u> No applicable information available.

# **Chronic Toxicity/Effects**

Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1-methoxypropan-2-ol

Assessment of repeated dose toxicity: May affect the liver as indicated in animal studies. The substance may cause damage to the kidney after repeated inhalation. Effect found in rodents only. The relevance to humans is questionable.

Information on: 2-dimethylaminoethanol

Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated ingestion of high doses. The results are preliminary and do not provide a complete understanding of the effect observed.

#### Information on: 1-methoxy-2-propylacetate

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

\_\_\_\_\_

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Revision date : 2019/08/28 Version: 4.0

#### **Carcinogenicity**

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

#### Information on: 2-dimethylaminoethanol

Assessment of carcinogenicity: Under certain conditions the substance can form nitrosamines. Nitrosamines are carcinogenic in animal studies. In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was not observed.

#### Information on: 2-butoxyethanol

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).

-----

#### Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

#### Information on: 1-methoxypropan-2-ol

Assessment of reproduction toxicity: The potential to impair fertility cannot be excluded when given at maternally toxic doses.

#### Information on: 2-dimethylaminoethanol

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The results were determined in a Screening test. On the basis of currently available information, a final assessment is not possible.

-----

#### **Teratogenicity**

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 1-methoxypropan-2-ol

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Information on: 2-dimethylaminoethanol Assessment of teratogenicity: Causes developmental effects in animals at high, maternally toxic doses.

-----

# Symptoms of Exposure

Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

# **12. Ecological Information**

No applicable information available.

Revision date : 2019/08/28 Version: 4.0

# 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

#### Container disposal:

WARNING: Empty containers may still contain hazardous residue. Dispose of in accordance with national, state and local regulations.

# **14. Transport Information**

Land transport USDOT	
Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT
<b>Sea transport</b> IMDG	
Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT
Air transport IATA/ICAO	
Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

# **15. Regulatory Information**

#### Federal Regulations

Registration status:ChemicalTSCA, USreleased / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

Revision date : 2019/08/28 Version: 4.0

Page: 11/12 (30660045/SDS GEN US/EN)

EPCRA 313:		
CAS Number	Chemical name	
111-76-2	2-butoxyethanol	

<u>State</u>	regulations	

State RTK	<u>CAS Nu</u>	umber	Chemical name
NJ	108-01-	0	2-dimethylaminoethanol
	107-98-	2	1-methoxypropan-2-ol
	111-76-	2	2-butoxyethanol
	7783-40	)-6	Magnesium fluoride (MgF2)
	7440-47	7-3	chromium
PA	108-01-	0	2-dimethylaminoethanol
	107-98-	2	1-methoxypropan-2-ol
	111-76-	2	2-butoxyethanol
	7783-40	)-6	Magnesium fluoride (MgF2)
	7440-47	7-3	chromium
NFPA Hazard Health: 3		activity: 0	Special:
HMIS III rating Health: 3¤	<b>)</b> Flammability: 3	Physica	l hazard:0

# 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2019/08/28

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION. DESIGNS. DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

# Safety Data Sheet 11-LE385 Magenta Shimmer Revision date : 2019/08/28

Version: 4.0

END OF DATA SHEET

Page: 12/12 (30660045/SDS\_GEN\_US/EN)