

A.T.F. CONDITIONER

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0103

OUTSTANDING FEATURES

- Helps fortify ATF against oxidation and acid formation.
- Helps keep seals soft and pliable
- Helps prevent the formation of sludge and varnish.
- Contains shear-resistant viscosity stabilizers to help maintain smooth shifting.

DESCRIPTION

MOC® Automatic Transmission Fluid Conditioner is an additive that contains a special detergent package to fortify ATF against oxidation, acid formation and breakdown due to thermal stress. The advanced formula contains synthetic base oils, shear-resistant viscosity stabilizers, dispersants and seal conditioners to help prevent deposits, erratic shifting and leaks. This "universal" conditioner is designed for use in the newest generation of ATF, including G.M., Dex, Ford Mercon, Chrysler, Nissan, Toyota and many other fluids

APPLICATION

Add to transmission at each service or when needed. Use between ATF fluid-exchanges.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear Oil
Color	-	Amber Yellow
Odor	-	Mild Petroleum
Specific Gravity @ 68°F	D1298	0.86
Density, U.S. (lbs/gal) @ 68°F (calculated)	-	7.18
Boiling Point (°F)	D1120	≥464
Flash Point (°F) (based on components)	D93	273

PACKAGING

Fill: 8 oz.

Case Quantity: 24

Case Weight: 14 lbs.