

# LIMITED-SLIP CONCENTRATE

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0149



## OUTSTANDING FEATURES

- Enhances limited-slip performance (anti-chatter) of rear axles.
- Compatible with most conventional and synthetic gear oils.
- Eliminates the need for inventory multiple gear oils.

## DESCRIPTION

Designed to prevent chatter in limited-slip differentials and full-time four-wheel drive transfer cases. This product helps quiet gears in the differential and fortify standard gear lubricants. It is designed to be used with any GL-5 gear lubricant in limited-slip applications. Recommended for rear-wheel drive passenger cars, trucks, and sport utility vehicles.

## APPLICATION

Add 1-part concentrate to every 25 parts of gear lubricant. Add treated gear lubricant to vehicle. Do not overfill system. For best results, use MOC® Limited-Slip Concentrate with MOC® Gear Guard™ #0148 or #0414 gear oil. Product may be added between services or as needed.

## SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Amber
Odor	-	Petroleum
Specific Gravity @ 68°F	D1298	.91
Density, U.S. (lbs/gal) @ 68°F		7.6
Viscosity, cSt @ 100°C	D445	~7
Viscosity, cSt @ 40°C	D445	~46
Viscosity Index	D2270	~108
Boiling Point(°F)	-	250
Flash Point(°F)PMCC	D93	≥ 257
% Phosphorus		1.6 - 2.0
% Nitrogen	D5291 Modified	0.9 - 1.1

## PACKAGING

**Fill:** 4 oz.

**Case Quantity:** 12

**Case Weight:** 3 lbs.

