

MULTI-VEHICLE SYNTHETIC ATF

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0411



OUTSTANDING FEATURES

- Full synthetic formula; not a synthetic blend.
- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Optimizes Inventory by eliminating the need to stock different types/brands of ATF.
- Conditions seals and helps prevent leaks.

DESCRIPTION

A special blend of fully synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the MOC® ATF Fluid Exchanger #94500 and ATF Cleaner/Supplement Kit #01941. [CLICK HERE TO VIEW THE VEHICLE APPLICATION GUIDE.](#)

APPLICATION

1.) Follow machine manufacturer's instructions. 2.) Fill oil-flush machine with manufacturer's specified amount of Engine Oil Power-Flushing Solution. Do not overfill. 3.) Refer to owner's manual for further information.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear
Color	-	Red
Specific Gravity @ 68°F	D1298	.84
Density, U.S. (lbs/gal) @ 68°F	-	7.06
Viscosity, cSt @ 40°C	D445	~33.2
Viscosity, cSt @ 100°C	D445	~6.44
Viscosity Index	D2270	149
Brookfield Viscosity @ -40°C, cP	D2983	~13,000
Pour Point °C	D97	-47

PACKAGING

Fill: 1 gal	Case Quantity: 4	Case Weight: 30 lbs.
Fill: 3 gal	Case Quantity: 2	Case Weight: 46 lbs.
Fill: 55 gal	Case Quantity: 1 Drum	Case Weight: 409 lbs.