

ULTRA SHIFT™

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0415



OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high-load conditions. Promotes excellent shift quality and synchronizer performance in manual transmissions.
- Compatible with manual transmission components such as bronze, brass, copper, and elastomer material.

DESCRIPTION

A full synthetic gear lubricant specially formulated for a wide range of manual transmissions, transaxles, and transfer cases. The combination of high-quality base oils and a multi-functional additive system in Ultra Shift™ provides superior anti-wear protection, shear stability and low temperature fluidity. This premium formula may be effectively used in all domestic and foreign vehicles where GL-4 gear oil or ATF is specified by the vehicle manufacturer. Ultra Shift™ is recommended in applications where GM® Part # 12345349, GM® Auto Trak II Part # 1237508, Toyota LF 75W 08885-81080, Ford® Part #D80Z19C547A & ESRY 19C547, Chrysler® Part #4773167, or Mercedes Benz® Part #900260315 are specified.

APPLICATION

Use quantity in accordance with vehicle manufacturer's recommendations.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear
Color	-	Yellow
Odor	-	Sulfur
Specific Gravity @ 68°F	D1298	0.85
Density, U.S. (lbs/gal) @ 68°F	D1250	7.09
Viscosity @ 100°C, cSt	D445	9.7
Viscosity, cSt @ 40°C	D445	43
Viscosity Index	D2270	221
Brookfield Viscosity @ -40°C, cP	D2983	21,795

PACKAGING

Fill: 1 qt.

Case Quantity: 12

Case Weight: 24 lbs.

