

# GEAR GUARD™ PLUS SAE 75W-90

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0427



## OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting, gear noise and corrosion under high-load conditions.
- Excellent fluidity and protection in extreme temperatures.
- Contains special additives to reduce chattering in limited-slip differentials.
- Meets stringent industry standards, including API GL-5, MT-1 and SAE J2360 specifications.
- Recommended for use where Ford M2C-192A, GM 12346140, Chrysler MS-8985, or GL-5 SAE 75W-90 gear oil is specified.

## DESCRIPTION

a multigrade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-90 viscosity. It is a premium extreme-pressure lubricant designed for use in axle applications requiring limited-slip performance but can also be used in conventional differentials. MOC® Gear Guard™ Plus SAE 75W-90 is a versatile product that can be used in place of SAE 75W-85, SAE 80w-90, SAE 90 oils and eliminates the need for supplemental friction modifiers such as Ford M2C118-A, Chrysler MS-5630, GM 1052358, GM 19351882. It is designed to provide excellent extreme pressure protection, load carrying capacity, anti-foam performance, corrosion protection, and thermal stability protection.

## APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ Plus is designed to be used in conjunction with MOC® Differential/Driveline service equipment and tools.

## SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Oil
Color	-	Amber
Odor	-	Petroleum
Specific Gravity @ 68°F	D1298	0.87
Density, U.S. (lbs/gal) @ 68°F	D1250	7.3
Viscosity @ 100°C, cSt	D445	16
Viscosity Index	D2270	120 (typical)
Brookfield Viscosity @ -40° C, cP	D2983	100,000

## PACKAGING

<b>Fill:</b> 1 quart	<b>Case Quantity:</b> 12 Bottles	<b>Case Weight:</b> 24.14 lbs.
<b>Fill:</b> 16 gal	<b>Case Quantity:</b> 1 drum	<b>Case Weight:</b> 125.1 lbs.