

HEAVY-DUTY DOT 4 BRAKE FLUID

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0601



OUTSTANDING FEATURES

- Contains special additives and esters for excellent high-temperature protection and moisture resistance.
- High-boiling point formula (ERBP of ~500°F).
- Exceeds DOT specifications for DOT 4 brake fluid (DOT minimum is 446°F).
- Two convenient sizes for use with fluid exchange equipment.
- Product can be mixed with other DOT 3 or DOT 4 products.

DESCRIPTION

A high quality product which meets and exceeds the DOT specifications for DOT 4 brake fluid.

APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear & Bright
Color	-	Light Yellow
Odor	-	Mild
Specific Gravity @ 68°F	D4052	1.05 - 1.06
Density, U.S. (lbs/gal) (Calculated)	-	8.80
Viscosity, cSt @ -40°C	D445	1,090
Dry ERBP, °F	SAE J-1703	~500
% Water	ASTM D6304	<0.3

PACKAGING

Fill: 32 oz.	Case Quantity: 12 Bottles	Case Weight: 29.6 lbs.
Fill: 53 oz.	Case Quantity: 4 Bottles	Case Weight: 16.39 lbs.