

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14  
Version: 3.0

Page: 1/14  
(30717573/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## 801-74 Elite Epoxy Prm BLK

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Flam. Liq.	2	Flammable liquids

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 2/14

(30717573/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs (Central nervous system, Kidney, Liver) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust or mist.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 3/14

(30717573/SDS\_GEN\_US/EN)

P501 Dispose of contents and container to hazardous or special waste collection point.

No applicable information available.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Acetone

CAS Number: 67-64-1  
Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: Acetone

n-butanol

CAS Number: 71-36-3  
Content (W/W):  $\geq 0.3$  -  $< 1.0\%$   
Synonym: 1-Butanol; n-Butanol

ethylbenzene

CAS Number: 100-41-4  
Content (W/W):  $\geq 0.3$  -  $< 1.0\%$   
Synonym: Ethylbenzene

2,6-dimethylheptan-4-one

CAS Number: 108-83-8  
Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: Diisobutyl ketone

2-heptanone

CAS Number: 110-43-0  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: 2-Heptanone; Methyl n-amyl ketone

Xylene

CAS Number: 1330-20-7  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: Xylene; Dimethylbenzene

butyl 2,3-epoxypropyl ether

CAS Number: 2426-08-6  
Content (W/W):  $\geq 0.3$  -  $< 1.0\%$   
Synonym: (Butoxymethyl)oxirane; Butyl glycidyl ether

trimethoxy(3-(oxiranylmethoxy)propyl)silane

CAS Number: 2530-83-8  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: Trimethoxy[3-(oxiranylmethoxy)propyl]silane; (3-Glycidoxypropyl)trimethoxysilane

Barium sulfate

CAS Number: 7727-43-7  
Content (W/W):  $\geq 25.0$  -  $< 50.0\%$   
Synonym: Barium sulfate, natural

talc

CAS Number: 14807-96-6  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 4/14

(30717573/SDS\_GEN\_US/EN)

Synonym: No data available.

Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)

CAS Number: 25068-38-6

Content (W/W): >= 3.0 - < 5.0%

Synonym: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane

aromatic epoxy compound MW < 700

CAS Number: 25036-25-3

Content (W/W): >= 0.3 - < 1.0%

Synonym: No data available.

4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene

CAS Number: 98-56-6

Content (W/W): >= 10.0 - < 15.0%

Synonym: No data available.

Aromatic epoxy compound

CAS Number: 25036-25-3

Content (W/W): >= 7.0 - < 10.0%

Synonym: No data available.

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

If irritation develops, seek medical attention. Wash affected areas with water for at least 15 minutes.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 5/14

(30717573/SDS\_GEN\_US/EN)

---

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Page: 6/14

Version: 3.0

(30717573/SDS\_GEN\_US/EN)

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), Stove-lacquer KNS L-5X, Stove-lacquer Valspar HXR008F red, Stove-lacquer RDL 50

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Formaldehyde	OSHA PEL	TWA value 0.75 ppm ; STEL value 2 ppm ; STEL value 2 ppm ; OSHA Action level 0.5 ppm ; TWA value 0.75 ppm ;
	ACGIH TLV	STEL value 0.3 ppm ; TWA value 0.1 ppm ;
Acetone	OSHA PEL	PEL 1,000 ppm 2,400 mg/m3 ; STEL value 1,000 ppm 2,400 mg/m3 ; TWA value 750 ppm 1,800 mg/m3 ;
	ACGIH TLV	TWA value 250 ppm ; STEL value 500 ppm ;
n-butanol	OSHA PEL	PEL 100 ppm 300 mg/m3 ; SKIN_FINAL ; The substance can be absorbed through the skin. CLV 50 ppm 150 mg/m3 ;
	ACGIH TLV	TWA value 20 ppm ;
Benzene	OSHA PEL	STEL value 5 ppm ; TWA value 1 ppm ; max. conc. 50 ppm ; CLV 25 ppm ; TWA value 10 ppm ; TWA value 1 ppm ; OSHA Action level 0.5 ppm ; STEL value 5 ppm ;
	ACGIH TLV	Skin Designation ; The substance can be absorbed through the skin. STEL value 2.5 ppm ; TWA value 0.5 ppm ;
ethylbenzene	OSHA PEL	PEL 100 ppm 435 mg/m3 ; TWA value 100 ppm 435 mg/m3 ; STEL value 125 ppm 545 mg/m3 ;
	ACGIH TLV	TWA value 20 ppm ;

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Page: 7/14

Version: 3.0

(30717573/SDS\_GEN\_US/EN)

2,6-dimethylheptan-4-one	OSHA PEL	PEL 50 ppm 290 mg/m <sup>3</sup> ; TWA value 25 ppm 150 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 25 ppm ;
2-heptanone	OSHA PEL	PEL 100 ppm 465 mg/m <sup>3</sup> ; TWA value 100 ppm 465 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 50 ppm ;
Xylene	OSHA PEL	PEL 100 ppm 435 mg/m <sup>3</sup> ; TWA value 100 ppm 435 mg/m <sup>3</sup> ; STEL value 150 ppm 655 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 100 ppm ; STEL value 150 ppm ;
butyl 2,3-epoxypropyl ether	OSHA PEL	PEL 50 ppm 270 mg/m <sup>3</sup> ; TWA value 25 ppm 135 mg/m <sup>3</sup> ;
	ACGIH TLV	Skin Designation ; The substance can be absorbed through the skin. TWA value 3 ppm ;
Barium sulfate	OSHA PEL	PEL 15 mg/m <sup>3</sup> Total dust ; PEL 5 mg/m <sup>3</sup> Respirable fraction ;
	ACGIH TLV	TWA value 5 mg/m <sup>3</sup> Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
talc		
	ACGIH TLV	TWA value 2 mg/m <sup>3</sup> Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

### **Advice on system design:**

Provide local exhaust ventilation to maintain recommended P.E.L.  
General mechanical ventilation should comply with OSHA 1910.94.

### **Personal protective equipment**

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.  
Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### **Hand protection:**

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 8/14

(30717573/SDS\_GEN\_US/EN)

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	of the solvent contained in the product	
Odour threshold:	No applicable information available.	
Colour:	black	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	56.00 - 169.00 °C 132.80 - 336.20 °F	
Sublimation point:	No applicable information available.	
Flash point:	6.67 °C 44.01 °F	
Flammability:	No applicable information available.	
Lower explosion limit:	0.80 %(V)	
Upper explosion limit:	12.80 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.8548 g/cm <sup>3</sup> ( 20 °C)	(calculated)
	15.4787 lb/USg ( 20 °C)	(calculated)
Relative density:	1.8548 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.500 mm <sup>2</sup> /s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.



# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 9/14

(30717573/SDS\_GEN\_US/EN)

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

#### *Information on: Acetone*

*Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. High concentrations in the air may cause narcosis.*

#### *Information on: n-butanol*

*Assessment of acute toxicity: Of low toxicity after short-term skin contact. Virtually nontoxic by inhalation. Of low toxicity after single ingestion. The European Union (EU) has classified this substance as 'harmful' after oral exposure. If used as intended, this product is not expected to present a physical or health hazard.*

#### *Information on: ethylbenzene*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.*

#### *Information on: 2-heptanone*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of moderate toxicity after single ingestion. Virtually nontoxic after a single skin contact.*

-----

#### Assessment other acute effects

No applicable information available.

#### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

#### *Information on: Acetone*

*Assessment of irritating effects: Irritating to eyes. Not irritating to the skin. Repeated exposure may cause skin dryness or cracking.*

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14  
Version: 3.0

Page: 10/14  
(30717573/SDS\_GEN\_US/EN)

*Information on: n-butanol*

*Assessment of irritating effects: Skin contact causes irritation. Risk of serious damage to eyes.*

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: 2,6-dimethylheptan-4-one*

*Assessment of irritating effects: Not irritating to eyes and skin.*

*Causes temporary irritation of the respiratory tract. May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: trimethoxy(3-(oxiranylmethoxy)propyl)silane*

*Assessment of irritating effects: May cause severe damage to the eyes. Not irritating to the skin.*

*Information on: talc*

*Assessment of irritating effects: Not irritating to eyes and skin.*

*Information on: Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

*Information on: 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene*

*Assessment of irritating effects: May cause slight irritation to the skin. Not irritating to the eyes.*

### Sensitization

*Assessment of sensitization: Sensitization after skin contact possible.*

*Information on: Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)*

*Assessment of sensitization:*

*Sensitization after skin contact possible.*

### Aspiration Hazard

No applicable information available.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

*Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.*

*Information on: Acetone*

*Assessment of repeated dose toxicity: The substance may cause damage to the testes after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the hematological system after repeated ingestion of high doses. The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.*

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 11/14

(30717573/SDS\_GEN\_US/EN)

*Information on: 2,6-dimethylheptan-4-one*

*Assessment of repeated dose toxicity: Based on available Data, the classification criteria are not met.*

*Information on: 2-heptanone*

*Assessment of repeated dose toxicity: No adverse effects were observed after repeated exposure in animal studies.*

*Information on: Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)*

*Assessment of repeated dose toxicity: Adaptive effects were observed after repeated exposure in animal studies.*

*Information on: 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene*

*Assessment of repeated dose toxicity: Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure.*

*May affect the liver and kidneys as indicated in animal studies. Overexposure may cause blood abnormalities.*

### Genetic toxicity

*Assessment of mutagenicity: The product has not been tested. The statement has been derived from the properties of the individual components.*

*Information on: Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)*

*Assessment of mutagenicity: The substance was mutagenic in a bacterial test system. The substance was mutagenic in a mammalian cell culture test system.*

### Carcinogenicity

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.*

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: talc*

*Assessment of carcinogenicity: Not classified, due to lack of data.*

### Reproductive toxicity

*Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.*

*Information on: Acetone*

*Assessment of reproduction toxicity: As shown in animal studies, the product may cause damage to the testes after repeated high exposures that cause other toxic effects.*

### Teratogenicity

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 12/14

(30717573/SDS\_GEN\_US/EN)

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

*Information on: n-butanol*

*Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.*

*The potential to cause toxicity to development cannot be excluded when given in high doses.*

---

## 12. Ecological Information

No applicable information available.

---

## 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

---

## 14. Transport Information

### Land transport

USDOT

Hazard class: 3  
Packing group: II  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

### Sea transport

IMDG

Hazard class: 3  
Packing group: II  
ID number: UN 1263  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: PAINT

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: II  
ID number: UN 1263  
Hazard label: 3

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 13/14

(30717573/SDS\_GEN\_US/EN)

Proper shipping name: PAINT

### 15. Regulatory Information

#### Federal Regulations

##### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

##### **EPCRA 313:**

<u>CAS Number</u>	<u>Chemical name</u>
100-41-4	ethylbenzene
1330-20-7	Xylene

#### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>	
NJ	67-64-1	Acetone	
	100-41-4	ethylbenzene	
	108-83-8	2,6-dimethylheptan-4-one	
	110-43-0	2-heptanone	
	1330-20-7	Xylene	
	7727-43-7	Barium sulfate	
	14807-96-6	talc	
	98-56-6	4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	
	PA	50-00-0	Formaldehyde
		67-64-1	Acetone
71-43-2		Benzene	
108-83-8		2,6-dimethylheptan-4-one	
110-43-0		2-heptanone	
1330-20-7		Xylene	
7727-43-7		Barium sulfate	
14807-96-6	talc		

#### **Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:**

**WARNING:** This product can expose you to chemicals including BENZENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### **NFPA Hazard codes:**

Health: 2      Fire: 3      Reactivity: 0      Special:

#### **HMIS III rating**

Health: 2 $\alpha$       Flammability: 3      Physical hazard: 0

### 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations

SDS Prepared on: 2020/02/14

# Safety Data Sheet

## 801-74 Elite Epoxy Prm BLK

Revision date : 2020/02/14

Version: 3.0

Page: 14/14

(30717573/SDS\_GEN\_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET